



PORTABLE WHOLE HOME/OFFICE SYSTEM



2017 Space Technology
Hall of Fame Inductee



description

- Self contained, portable, multiple technologies, whole home/office air system
- Plugs into standard 120VAC outlet
- Adjustable purifier control and fan speed
- LCD status display of machine
- All settings are remote control adjusted only
- Away mode features with adjustable digital timer
- 5 speed fan control; 12 step purifier control

applications

- For reduction or removal of typical indoor air pollutants such as: visible smoke, odors, and microbials on **surfaces***
- Removes dirt and dust from the air
- Freshens air and removes odors
- School classrooms
- Nursing homes
- Public lobbies and waiting rooms

the technology

The AP3000 substantially reduces odors, visible smoke from the air, and microbial populations on **surfaces,*** commonly found in the average home or office environment. AP3000 also utilizes needlepoint ionization, pulsating negative/positive ion field generator,

corona discharge air freshener, and the patent pending ActivePure® Technology – consisting of a special UV light and photocatalyst target – thereby creating an Advanced Oxidation Plasma containing several friendly oxidizers.

*Published scientific studies conducted on behalf of activTek by Dr. James Marsden at Kansas State University demonstrated that activTek's ActivePure® Technology substantially reduces microbial populations on surfaces. The study's results are being provided solely for informational purposes. The study's results have not been reviewed by the FDA, EPA or any other governmental agency. Our products are not medical devices and are not intended to diagnose, treat, or cure any disease. We make no claims and no claims should be inferred as to the efficacy of our products to sanitize, disinfect or kill germs or other antimicrobials.

specifications

AP3000	9940040 – NOTE: This unit does not meet California requirements and cannot be shipped to California	
AP3000 II	9940039 (ozone free)* Model A1011B – Meets California ozone emissions limit. CARB Certified.	
electrical	Input Voltage: 100 ~ 240 VAC 50/60 Hz External Power Supply 48 watts	Current: 50 Watts Max
mechanical	40-60 CFM Fan, Washable electrostatic lint screen	computer style cord
dimensions	12" H x 9" W x 12" D	30.5cm H x 23cm W x 30.5cm D
weight	10.2 lbs.	4.62 kilograms
coverage	250 sq. ft. to 3,000 sq. ft.	
warranty	Limited 3 year warranty	